

TESTING LABORATORY

Nr

050/16

Date of Edition

2016-03-01

Page

1 / 10

Applicant

BISELARTE – Sociedade de Vidros, Lda.
Zona Industrial de Oiã – Apartado 100
3770-908 – OIÃ - PORTUGAL

Date of Entry

2016-02-12

Appliance / Product Tested**Nr of Samples**

Designation: Fixed luminaire - Bathroom mirror.
Manufacturer/Trademark ...: XPCS
Reference: ANNA 1000x800
Ratings: 230V; 50Hz; 16,1W LED; IP44; Class II, 30W (heating)
Observations: ----

1

Manufacturer / Representative

BISELARTE – Sociedade de Vidros, Lda.
Zona Industrial de Oiã – Apartado 100
3770-908 – OIÃ - PORTUGAL

Standards / Reference Documents

EN 62321 (2013)

Type / Scope of Test

Tests to check compliance of used materials according to specified reference documents by X-ray fluorescent (XRF) spectrometry executed with NITON trademark equipment type reference XLt 797Y.

Test Result

The test results are described in the following pages.

Bathroom mirror family with the same components

ANNA 1000x600;	TURÍS 1000X800 ;
ANNA 800x600;	TURÍS 900X600 ;
GANDIA 800X600 ;	TURÍS 800X600 ;
GANDIA 700X600 ;	HITA 800X600


Test Performed by


João Lopes
(Laboratory Technical)

Date

2016-03-01

Approved by


Manuel Farias
(Executive Director)

Date

2016-03-01

Photographs:





General remarks:

Throughout this report a comma is used as the decimal separator.

Test case verdicts:

- Test with non conclusive results : Inconclusive
- Test item does meet the requirement : Pass
- Test item does not meet the requirement : Fail


Marking plate:




Handwritten signature

Measured values are as follows:

Metal parts

Item	Corner support plate	Lead (Pd)	Cadmium (Cd)	Mercury (Hg)	Chromium (Cr) (1)	Bromine (Br) (2)	Result
	Measured value (ppm)	N/D	N/D	N/D	N/D	N/D	Pass
	Máximum value (ppm) +30%	1 000	100	1 000	1 000	1 000	

Item	Plate (7688)	Lead (Pd)	Cadmium (Cd)	Mercury (Hg)	Chromium (Cr) (1)	Bromine (Br) (2)	Result
	Measured value (ppm)	N/D	N/D	N/D	N/D	N/D	Pass

Terminal Block

Item	Plastic housing	Lead (Pd)	Cadmium (Cd)	Mercury (Hg)	Chromium (Cr) (1)	Bromine (Br) (2)	Result
	Measured value (ppm)	N/D	N/D	N/D	N/D	N/D	Pass
	Máximum Value (ppm) +30%	1 000	100	1 000	1 000	1 000	

Item	Black rubber	Lead (Pd)	Cadmium (Cd)	Mercury (Hg)	Chromium (Cr) (1)	Bromine (Br) (2)	Result
	Measured value (ppm)	70	2	N/D	N/D	4	Pass
	Máximum Value (ppm) +30%	1 000	100	1 000	1 000	1 000	

Item	Screw	Lead (Pd)	Cadmium (Cd)	Mercury (Hg)	Chromium (Cr) (1)	Bromine (Br) (2)	Result
	Measured value (ppm)	457	N/D	N/D	N/D	N/D	Pass
	Máximum Value (ppm) +30%	1 000	100	1 000	1 000	1 000	

Insulating fittings

Item	White Thermo Shrink Tube	Lead (Pd)	Cadmium (Cd)	Mercury (Hg)	Chromium (Cr) (1)	Bromine (Br) (2)	Result
	Measured value (ppm)	N/D	N/D	N/D	90	N/D	Pass
	Máximum Value (ppm) +30%	1 000	100	1 000	1 000	1 000	

Item	Self Adhesive Fixing Cable	Lead (Pd)	Cadmium (Cd)	Mercury (Hg)	Chromium (Cr) (1)	Bromine (Br) (2)	Result
	Measured value (ppm)	N/D	N/D	N/D	N/D	N/D	Pass
	Máximum Value (ppm) +30%	1 000	100	1 000	1 000	1 000	

Item	White cable ties	Lead (Pd)	Cadmium (Cd)	Mercury (Hg)	Chromium (Cr) (1)	Bromine (Br) (2)	Result
	Measured value (ppm)	N/D	N/D	N/D	N/D	N/D	Pass
	Máximum Value (ppm) +30%	1 000	100	1 000	1 000	1 000	

Anchorage cord

Item	Anchorage cord	Lead (Pd)	Cadmium (Cd)	Mercury (Hg)	Chromium (Cr) (1)	Bromine (Br) (2)	Result
	Measured value (ppm)	294	N/D	353	N/D	N/D	Pass
	Máximum Value (ppm) +30%	1 000	100	1 000	1 000	1 000	

Terminal splice

Item	Red cover	Lead (Pd)	Cadmium (Cd)	Mercury (Hg)	Chromium (Cr) (1)	Bromine (Br) (2)	Result
	Measured value (ppm)	N/D	N/D	N/D	N/D	N/D	Pass
	Maximum Value (ppm) +30%	1 000	100	1 000	1 000	1 000	

Item	Coupler	Lead (Pd)	Cadmium (Cd)	Mercury (Hg)	Chromium (Cr) (1)	Bromine (Br) (2)	Result
	Measured value (ppm)	294	N/D	353	N/D	N/D	Pass
	Maximum Value (ppm) +30%	1 000	100	1 000	1 000	1 000	

Led Strip

Item	Led Strip	Lead (Pd)	Cadmium (Cd)	Mercury (Hg)	Chromium (Cr) (1)	Bromine (Br) (2)	Result
	Measured value (ppm)	795	8	N/D	N/D	23	Pass
	Máximum Value (ppm) +30%	1 000	100	1 000	1 000	1 000	

Item	Insulation of wiring (red)	Lead (Pd)	Cadmium (Cd)	Mercury (Hg)	Chromium (Cr) (1)	Bromine (Br) (2)	Result
	Measured value (ppm)	12	42	N/D	N/D	4	Pass
	Máximum Value (ppm) +30%	1 000	100	1 000	1 000	1 000	

Item	Insulation of wiring (black)	Lead (Pd)	Cadmium (Cd)	Mercury (Hg)	Chromium (Cr) (1)	Bromine (Br) (2)	Result
	Measured value (ppm)	43	31	N/D	N/D	8	Pass
	Máximum Value (ppm) +30%	1 000	100	1 000	1 000	1 000	

Item	Cooper of wiring	Lead (Pd)	Cadmium (Cd)	Mercury (Hg)	Chromium (Cr) (1)	Bromine (Br) (2)	Result
	Measured value (ppm)	127	N/D	N/D	N/D	N/D	Pass
	Máximum Value (ppm) +30%	1 000	100	1 000	1 000	1 000	

Item	Silicon	Lead (Pd)	Cadmium (Cd)	Mercury (Hg)	Chromium (Cr) (1)	Bromine (Br) (2)	Result
	Measured value (ppm)	N/D	N/D	N/D	N/D	N/D	Pass
	Máximum Value (ppm) +30%	1 000	100	1 000	1 000	1 000	

Item	White thermoshrinkable sleeve	Lead (Pd)	Cadmium (Cd)	Mercury (Hg)	Chromium (Cr) (1)	Bromine (Br) (2)	Result
	Measured value (ppm)	N/D	N/D	N/D	21	N/D	Pass
	Máximum Value (ppm) +30%	1 000	100	1 000	1 000	1 000	

Handwritten signature

Connector

Item	Red cover	Lead (Pd)	Cadmium (Cd)	Mercury (Hg)	Chromium (Cr) (1)	Bromine (Br) (2)	Result
	Measured value (ppm)	N/D	N/D	N/D	N/D	N/D	Pass
	Máximum Value (ppm) +30%	1 000	100	1 000	1 000	1 000	

Black internal cable

Item	External sheathing	Lead (Pd)	Cadmium (Cd)	Mercury (Hg)	Chromium (Cr) (1)	Bromine (Br) (2)	Result
	Measured value (ppm)	N/A	N/D	N/D	N/D	N/D	Pass
	Máximum Value (ppm) +30%	1 000	100	1 000	1 000	1 000	

Item	Basic insulation of conductors (brown)	Lead (Pd)	Cadmium (Cd)	Mercury (Hg)	Chromium (Cr) (1)	Bromine (Br) (2)	Result
	Measured value (ppm)	N/D	N/D	N/D	N/D	N/D	Pass
	Máximum Value (ppm) +30%	1 000	100	1 000	1 000	1 000	

Item	Basic insulation of conductors (blue)	Lead (Pd)	Cadmium (Cd)	Mercury (Hg)	Chromium (Cr) (1)	Bromine (Br) (2)	Result
	Measured value (ppm)	N/D	N/D	N/D	N/D	N/D	Pass
	Máximum Value (ppm) +30%	1 000	100	1 000	1 000	1 000	

Item	Copper	Lead (Pd)	Cadmium (Cd)	Mercury (Hg)	Chromium (Cr) (1)	Bromine (Br) (2)	Result
	Measured value (ppm)	321	N/D	N/D	N/D	N/D	Pass
	Máximum Value (ppm) +30%	1 000	100	1 000	1 000	1 000	

Converter


Item	Plastic housing	Lead (Pd)	Cadmium (Cd)	Mercury (Hg)	Chromium (Cr) (1)	Bromine (Br) (2)	Result
	Measured value (ppm)	N/D	N/D	N/D	N/D	N/D	Pass
	Máximum Value (ppm) +30%	1 000	100	1 000	1 000	1 000	

Item	Print circuit board	Lead (Pd)	Cadmium (Cd)	Mercury (Hg)	Chromium (Cr) (1)	Bromine (Br) (2)	Result
	Measured value (ppm)	258	N/D	N/D	N/D	N/D	Pass
	Máximum Value (ppm) +30%	1 000	100	1 000	1 000	1 000	

Item	Resistances	Lead (Pd)	Cadmium (Cd)	Mercury (Hg)	Chromium (Cr) (1)	Bromine (Br) (2)	Result
	Measured value (ppm)	N/D	N/D	N/D	422	N/D	Pass
	Máximum Value (ppm) +30%	1 000	100	1 000	1 000	1 000	

Item	Terminals	Lead (Pd)	Cadmium (Cd)	Mercury (Hg)	Chromium (Cr) (1)	Bromine (Br) (2)	Result
	Measured value (ppm)	621	3	N/D	74	N/D	Pass
	Máximum Value (ppm) +30%	1 000	100	1 000	1 000	1 000	

Item	Electrolytic capacitors	Lead (Pd)	Cadmium (Cd)	Mercury (Hg)	Chromium (Cr) (1)	Bromine (Br) (2)	Result
	Measured value (ppm)	N/D	N/D	N/D	N/D	N/D	Pass
	Máximum Value (ppm) +30%	1 000	100	1 000	1 000	1 000	


Item	Polyester capacitors	Lead (Pd)	Cadmium (Cd)	Mercury (Hg)	Chromium (Cr) (1)	Bromine (Br) (2)	Result
	Measured value (ppm)	N/D	N/D	N/D	N/D	N/D	Pass
	Máximum Value (ppm) +30%	1 000	100	1 000	1 000	1 000	

Item	Coils	Lead (Pd)	Cadmium (Cd)	Mercury (Hg)	Chromium (Cr) (1)	Bromine (Br) (2)	Result
	Measured value (ppm)	375	31	N/D	N/D	182	Pass
	Máximum Value (ppm) +30%	1 000	100	1 000	1 000	1 000	

At

Item	Ceramic capacitors	Lead (Pd)	Cadmium (Cd)	Mercury (Hg)	Chromium (Cr) (1)	Bromine (Br) (2)	Result
	Measured value (ppm)	N/D	N/D	N/D	182	35	Pass
	Máximum Value (ppm) +30%	1 000	100	1 000	1 000	1 000	

Item	Diodes	Lead (Pd)	Cadmium (Cd)	Mercury (Hg)	Chromium (Cr) (1)	Bromine (Br) (2)	Result
	Measured value (ppm)	N/D	N/D	N/D	68	N/D	Pass
	Máximum Value (ppm) +30%	1 000	100	1 000	1 000	1 000	

Item	Integrated circuit	Lead (Pd)	Cadmium (Cd)	Mercury (Hg)	Chromium (Cr) (1)	Bromine (Br) (2)	Result
	Measured value (ppm)	N/A	N/A	19	52	36	Pass
	Máximum Value (ppm) +30%	1 000	100	1 000	1 000	1 000	

Item	Transistors	Lead (Pd)	Cadmium (Cd)	Mercury (Hg)	Chromium (Cr) (1)	Bromine (Br) (2)	Result
	Measured value (ppm)	606	N/D	N/D	N/D	N/D	Pass
	Máximum Value (ppm) +30%	1 000	100	1 000	1 000	1 000	

white internal cable

Item	External sheathing	Lead (Pd)	Cadmium (Cd)	Mercury (Hg)	Chromium (Cr) (1)	Bromine (Br) (2)	Result
	Measured value (ppm)	N/A	N/D	N/D	N/D	N/D	Pass
	Máximum Value (ppm) +30%	1 000	100	1 000	1 000	1 000	

Item	Basic insulation of conductors (brown)	Lead (Pd)	Cadmium (Cd)	Mercury (Hg)	Chromium (Cr) (1)	Bromine (Br) (2)	Result
	Measured value (ppm)	N/D	N/D	N/D	N/D	N/D	Pass
	Máximum Value (ppm) +30%	1 000	100	1 000	1 000	1 000	

Handwritten signature

Item	Basic insulation of conductors (blue)	Lead (Pd)	Cadmium (Cd)	Mercury (Hg)	Chromium (Cr) (1)	Bromine (Br) (2)	Result
	Measured value (ppm)	N/D	N/D	N/D	N/D	N/D	Pass
	Máximum Value (ppm) +30%	1 000	100	1 000	1 000	1 000	

Item	Copper	Lead (Pd)	Cadmium (Cd)	Mercury (Hg)	Chromium (Cr) (1)	Bromine (Br) (2)	Result
	Measured value (ppm)	321	N/D	N/D	N/D	N/D	Pass
	Máximum Value (ppm) +30%	1 000	100	1 000	1 000	1 000	

Heater


Item	Transparent film	Lead (Pd)	Cadmium (Cd)	Mercury (Hg)	Chromium (Cr) (1)	Bromine (Br) (2)	Result
	Measured value (ppm)	N/D	N/D	N/D	N/D	N/D	Pass
	Máximum value (ppm) +30%	1 000	100	1 000	1 000	1 000	

Item	Supplementary insulation of conductors (black)	Lead (Pd)	Cadmium (Cd)	Mercury (Hg)	Chromium (Cr) (1)	Bromine (Br) (2)	Result
	Measured value (ppm)	650	N/D	N/D	N/D	N/D	Pass
	Máximum Value (ppm) +30%	1 000	100	1 000	1 000	1 000	

Item	Supplementary insulation of conductors (blue)	Lead (Pd)	Cadmium (Cd)	Mercury (Hg)	Chromium (Cr) (1)	Bromine (Br) (2)	Result
	Measured value (ppm)	672	N/D	N/D	N/D	N/D	Pass
	Máximum Value (ppm) +30%	1 000	100	1 000	1 000	1 000	

Item	Copper of conductors	Lead (Pd)	Cadmium (Cd)	Mercury (Hg)	Chromium (Cr) (1)	Bromine (Br) (2)	Result
	Measured value (ppm)	N/D	N/D	N/D	N/D	N/D	Pass
	Máximum Value (ppm) +30%	1 000	100	1 000	1 000	1 000	

Item	Tape thermo formable	Lead (Pd)	Cadmium (Cd)	Mercury (Hg)	Chromium (Cr) (1)	Bromine (Br) (2)	Result
	Measured value (ppm)	N/D	N/D	N/D	N/D	9	Pass
	Máximum Value (ppm) +30%	1 000	100	1 000	1 000	1 000	

Item	Film with heating element	Lead (Pd)	Cadmium (Cd)	Mercury (Hg)	Chromium (Cr) (1)	Bromine (Br) (2)	Result
	Measured value (ppm)	N/D	N/D	N/D	N/D	N/D	Pass
	Máximum Value (ppm) +30%	1 000	100	1 000	1 000	1 000	

Item	Basic insulation of conductors	Lead (Pd)	Cadmium (Cd)	Mercury (Hg)	Chromium (Cr) (1)	Bromine (Br) (2)	Result
	Measured value (ppm)	795	N/D	N/D	N/D	N/D	Pass
	Máximum Value (ppm) +30%	1 000	100	1 000	1 000	1 000	

N/D – No detected

- 1) Measured values represents existing total chromium.
- 2) Measured values represents the total polybrominated materials.

Handwritten signature